## TIRET 100 IP40 Recessed linear downlights



	151TDT 1 1700
	151TRT.1-I728
	Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.
	Linear fixture in 582mm length and in a width of 54mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
	Opal extruded polycarbonate diffuser. Highly efficient linear printed circuit board.
	Accessories available to create customized linear systems.
	Built-in driver, included. Electronic options for lighting control: DALI-2.
	Passive temperature management. Ceiling-mounted using steel support with screws.
	Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized
	systems.
<sup>3</sup> FJ <sup>*</sup> <sup>5</sup>	Luminaire luminous flux:     655lm     Imax=291 cd     n=100.0%     V     V     V     91°       Luminaire connected power:     7.1 W     1     2.0     291
	Luminaire efficiency: 92 lm/W
	Light source luminous flux: 1040lm Light source power: 6 W
	Constant Current: 150 mA CRI: 90
	Colour Temperature: 3000K 275 5 10.2 11.6
	Chromaticity Tolerance: MacAdam 3 Beam Angle: 91°
	LOR: 63% Average Service Life: 50000h
	LED reliability: >72000h L80B10 UGR: <19 under the below indicated parameters
	Room Green Sale Alter Sa
	Luminaire spacing = 0.45m Photobiological safety group: 1
	Cd/Klm: 443 This product contains a light source of energy efficiency class D
	S: On/Off (AC/DC) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi
	*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.05.2024]

## 5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

## Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com