RAINA 100 IP40 Recessed linear downlights



	150RNA.1-I1127
	IP40 650° FAL +ADULAR 295 x 58mm
	Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.
	Linear fixture in 306mm length and in a width of 68mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser.
	Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2.
	The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: $PstLM \le 1$ and $SVM \le 0.4$. Passive temperature management.
	Ceiling-mounted using steel support with screws. End caps must be ordered separately, reference M5.E0068. It is possible to combine different lengths to create customized design. The connection accessory must
3⊧ <u> </u>	be ordered separately, reference M5.Q0068. Luminaire luminous flux: 333lm Imax=125 cd n=100.0% V M V Ø VLUX 103°
	Luminaire connected power: 4,81 W Luminaire efficiency: 69 lm/W Light source luminous flux: 555lm
	Light source power: 3,21 W Constant Current: 150 mA CRI: 90
	Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 103°
10 F	LOR: 60% Average Service Life: 50000h LED reliability: >72000h L80B10
306	Photobiological safety group: 1 This product contains a light source of energy efficiency class D
	Electronic Equipment S: On/Off D: DALI-2/switchDIM B: Bluetooth-Casambi
	*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. Finishes
	2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.05.2024]

5 years guarantee E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

08540 Centelles | Barcelona

Contact Ronda de la Font Grossa, 15 T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com