RAINA 200

IP40 Frameless recessed linear downlights









250RNA.1-I1130









Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 290mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

Passive temperature management.

Ceiling-mounted using steel support with screws.

End caps must be ordered separately, reference M5.E0055.

It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.P0055.

lmax=242 Cd

135

η=100.0% ▼ M ▼ Ø ▼LUX

2 5.0 60

3 7.5 27

4 10.0 15.1

> 12.5 9.7

103°

242 2.5

Luminaire luminous flux: 645lm Luminaire connected power: 7,16 W Luminaire efficiency: 90 lm/W Light source luminous flux: 1075lm Light source power: 5,46 W Constant Current: 250 mA

CRI: 80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 103°

LOR: 60%

Average Service Life: 50000h LED reliability: >72000h L80B10 Photobiological safety group: 1

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off D: DALI-2/switchDIM B: Bluetooth-Casambi

*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13