RAINA 300 IP40 Surface mounted linear downlights



	350RNA.1-I1126
	IP40 650° +RAL
	Surface mounted linear fixtures with symmetrical light distribution to achieve an effective task or general
	lighting. Linear fixture in 290mm length and in a width of 55mm.
	Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser.
	Highly efficient linear printed circuit board.
	Built-in driver, included. Electronic options for lighting control: DALI-2.
	The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker
	limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management.
	Ceiling-mounted using cleats. End caps must be ordered separately, reference M5.E0055.
	It is possible to combine different lengths to create customized design. The connection accessory must
]75	be ordered separately, reference M5.A.
290	Luminaire luminous flux: 318 lm Luminaire connected power: $4,81$ W Luminaire efficiency: 66 lm/W Light source luminous flux: 530 lm Light source power: $3,21$ W Constant Current: 150 mA CRI: 90 Colour Temperature: 3000 K Chromaticity Tolerance: MacAdam 3 Beam Angle: 103°
	LOR: 60%
⁴]55]	Average Service Life: 50000h LED reliability: >72000h L80B10 Photobiological safety group: 1 This product contains a light source of energy efficiency class D
	Electronic Equipment
	S: On/Off D: DALI-2/switchDIM
	 B: Bluetooth-Casambi *Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.
	Finishes
	2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.05.2024]

5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com