RAINA 600

IP40 Wall-mounted linear fixtures









650RNA.1-I1131







Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general

Linear fixture in 290mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

Passive temperature management. Wall mounted by mounting brackets.

End caps must be ordered separately, reference M5.E0055.

It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.U.

lmax=244 Cd

135

180

η=100.0% ▼ M ▼ Ø ▼LUX

1 2.5 244

2 5.0 61

3 7.5 27

4 10.0 15.2

> 12.5 9.8

103°

Luminaire luminous flux: 651lm Luminaire connected power: 7,16 W Luminaire efficiency: 91 lm/W Light source luminous flux: 1085lm Light source power: 5,46 W Constant Current: 250 mA

CRI: 80

Colour Temperature: 5000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 103°

LOR: 60%

Average Service Life: 50000h LED reliability: >72000h L80B10 Photobiological safety group: 1

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off D: DALI-2/switchDIM

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 30.04.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13