
RAINA 800 **IP40 Projectors**









850RNA.1-I1129



IP40 6509





Linear projectors with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 290mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

lmax=229 Cd

Passive temperature management.

Ceiling or wall installation with adjustable fixing brackets.

Luminaire luminous flux: 612lm Luminaire connected power: 7,16 W Luminaire efficiency: 85 lm/W Light source luminous flux: 1020lm Light source power: 5,46 W

Constant Current: 250 mA **CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 103°

LOR: 60%

Average Service Life: 50000h LED reliability: >72000h L80B10 Photobiological safety group: 1

This product contains a light source of energy efficiency class C

1 2.5 229 2 5.0 57 3 7.5 25 135 4 10.0 14.3 5 12.5 9.2

η=100.0% ▼ M ▼ Ø ▼LUX

103°

Electronic Equipment

S: On/Off

D: DAI I-2/switchDIM

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 01.05.2025]

5 years guarantee



Spain

T. +34 93 881 37 13