BARIS 200



IP54 Frameless recessed linear downlights

IP54 IK08 650° +HAL ▶ +MODULAR ▶ Expression 288 x 47mm ▲
Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective
task or general lighting. Frameless linear fixture in 287mm length and in a width of 44mm.
Protection rating against dust and moisture: complete IP54. Protection rating of resistance to harmful mechanical impacts: IK08.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser.
Highly efficient linear printed circuit board. Built-in driver, included.
Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker
limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management.
Ceiling-mounted using steel support with screws.Pre-wiring of 35cm cable 3x1mm2. Accessory for serial installation, reference F3.L2.BRS.
Luminaire luminous flux: 350lmImmeria connected power: 4,81 WImmeria connected power: 4,81 WImmeria connected power: 4,81 WLight source luminous flux: 660lmLight source power: 3,21 WImmeria connected power: 3,21 WImmeria connected power: 3,21 WConstant Current: 150 mACRI: 80Colour Temperature: 4000KImmeria connected power: 4,81 WColour Temperature: 4000KChromaticity Tolerance: MacAdam 3Immeria connected power: 4,81 WDeres 53%Average Service Life: 50000hImmeria connected power: 1,100 MLED reliability: >72000h L80B10Photobiological safety group: 1This product contains a light source of energy efficiency class CElectronic EquipmentBillet source of energy efficiency class CElectronic EquipmentBillet source to indicate your electronic equipment choice.Mith - S, -D, -B after the reference to indicate your electronic equipment choice.Add the suffix -S, -D, -B after the reference fore, 7: ENL9006: White Aluminium, 1: ENL9010: Pure White
Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.05.2024]

5 years guarantee E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com