
HORIZON 200

IP20 Frameless recessed linear downlights







220HRN.1-I1274



IP20 650°









Imax=2507 Cd

η=100.0% ▼ M ▼ Ø ▼LUX

2 1.11

3 1.67 279

4 2.2 157

0.56 2507

2.8 100

31°

Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 295mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: $PstLM \le 1$ and $SVM \le 0.4$.

Passive temperature management.

Ceiling-mounted using steel support with screws.

Pre-wiring of 35cm cable 3x1mm2.

It is possible to combine different lengths and junction modules in different ways to create customized design.

Luminaire luminous flux: 1217lm Luminaire connected power: 6,9 W Luminaire efficiency: 176 lm/W Light source luminous flux: 1255lm

Light source power: 6,9 W **Constant Current:** 500 mA

CRI: 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 31° LOR: 97%

Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off

D: DALI-2/switchDIM

B: Bluetooth-Casambi

*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASIS.L.

info@rovasi.com

T. +34 93 881 35 12 T. +34 93 881 37 13