## HORIZON 200



## IP20 Frameless recessed linear downlights

220HRN.1-I1276
IP20     650°     +RAL     +MODULAR       ►     ►     ►       ►     ►     ►       ∠296 x 53mm     ✓
Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Frameless linear fixture in 295mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM $\leq$ 1 and SVM $\leq$ 0.4. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized design.
-
Luminaire luminous flux: 1314lm Luminaire connected power: $6,9 \text{ W}$ Luminaire efficiency: $190 \text{ Im}/W$ Light source luminous flux: 1355lm Light source power: $9,9 \text{ W}$ Constant Current: $500 \text{ mA}$ CRI: $80$ Colour Temperature: $5000\text{K}$ Chromaticity Tolerance: MacAdam 3 Beam Angle: $31^{\circ}$ LOR: $97\%$ Average Service Life: $50000\text{h}$ LED reliability: >54000h L80B10 Photobiological safety group: 1 This product contains a light source of energy efficiency class C Electronic Equipment 8:  On/Off 9:  OAL-2/switchDIM B: Bluetooth-Casambi 'Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. Finishes $2:  RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White$
Upgradeable, Replaceable, Repairable

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.05.2024]

**CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.** Ronda de la Font Grossa, 15

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

## Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com