# GOWEL 200

## IP20 Frameless recessed linear downlights







### 200GWL.1-I1281



IP20 **IK06** 650°









Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 295mm length and in a width of 70mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.

Ceiling-mounted using steel support with screws.

Pre-wiring of 35cm cable 3x1mm2.

It is possible to combine different lengths and junction modules in different ways to create customized systems.

Imax=5112 Cd

η=100.0% ▼ M ▼ Ø ▼ LUX

0.30 5112

0.61 1278

568

0.91 3

> 1.21 320

Luminaire luminous flux: 805lm Luminaire connected power: 4,4 W Luminaire efficiency: 183 lm/W Light source luminous flux: 885lm Light source power: 4,4 W Constant Current: 150 mA

**CRI:** 80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 17° **LOR:** 91%

Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1

This product contains a light source of energy efficiency class C

#### **Electronic Equipment**

S: On/Off

D: DALI-2/switchDIM

B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

#### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.05.2024]

5 years guarantee



Spain

T. +34 93 881 37 13