GOWEL 300



IP20 Surface mounted linear downlights

	300GWL.1-I1288
	Surface mounted linear downlights with symmetrical light distribution to achieve an effective task or
	general lighting.
	Linear fixture in 295mm length and in a width of 70mm.
	Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
	Range of PMMA optics to achieve specific photometric results.
	Highly efficient linear printed circuit board. Accessories available to create customized linear systems.
	Built-in driver, included.
	Electronic options for lighting control: DALI-2.
	The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker
	limits: PstLM \leq 1 and SVM \leq 0.4.
	Passive temperature management.
	Ceiling-mounted using cleats.
	It is possible to combine different lengths and junction modules in different ways to create customized
]65	systems.
295	
200	Luminaire luminous flux: 2594lm
	Luminaire connected power: 16 W
	Luminaire efficiency: 162 lm/W
	Light source power: 16 W Constant Current: 500 mA
	CRI: 80
	Colour Temperature: 5000K
	Chromaticity Tolerance: MacAdam 3
	Beam Angle: 17°
	LOR: 91%
	Average Service Life: 50000h
	LED reliability: >54000h L80B10
	Photobiological safety group: 1
	This product contains a light source of energy efficiency class C
	Electronic Equipment S: On/Off
	D: DALI-2/switchDIM
	B: Bluetooth-Casambi
	*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	2: RAL9000. Jet Diack, 4: RAL7010. Antinacite Grey, 7: RAL9000. White Authinition, 1: RAL9010. Pure White
	Upgradeable, Replaceable, Repairable
I	

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.05.2024]

5 years guarantee E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com