Trimless appearance recessed downlights



η=99.9% ▼ M ▼ Ø ▼ LUX

1

2 0.61 945

3 0.92 420


4 1.22 236

5 1.53 151

0.31 3780

17°





107BXS.1-R1809



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

Round design with trimless appearance in diameter 72mm.

Aluminium body and interior circle powder painted in various finishes, customized RAL under request. To complete the effect of this luminaire, it is suggested that the circle be painted the same RAL colour as the ceiling.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035]. Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].

Remote driver included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

Imax=3780 Cd

3 hours battery available as option*.

Passive temperature management: heat dissipation via aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 734lm Luminaire connected power: 8,91 W Luminaire efficiency: 82 lm/W Light source luminous flux: 1080lm Light source power: 8,02 W Constant Current: 250 mA

CRI: >90 R9 62

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 17° **LOR:** 68%

LED reliability at nominal Ta = 25°C: 60.000h L90B10

Photobiological safety group: 1

This product contains a light source of energy efficiency class E

Electronic Equipment

K: On/Off (basic) S: On/Off (AC/DC

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 06.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13