


108BSS.1-R1809



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.
Square design with frameless appearance in 80mm x 80mm.
Aluminium body and interior powder painted in various finishes, customized RAL under request.
To complete the effect of this luminaire, it is suggested that the interior be painted the same RAL colour as the ceiling.
Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].
Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].
Remote driver included.
Electronic options for lighting control: DALI-2.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
3 hours battery available as option*.
Passive temperature management: heat dissipation via aluminium heat sink.
Ceiling-mounted using galvanised steel support with spring clamps.

Luminaire luminous flux: 756lm
Luminaire connected power: 8,91 W
Luminaire efficiency: 85 lm/W
Light source luminous flux: 1080lm
Light source power: 8,02 W
Constant Current: 250 mA
CRI: >90 R9 62
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 28°
LOR: 70%

LED reliability at nominal Ta = 25°C: 100.000h L90B50 | 50.000h L90B10
Photobiological safety group: 1
This product contains a light source of energy efficiency class E


Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC, NOT looping through capable)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery
B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com