
IP65 Small recessed downlights







101SEL.1.01-R2316



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Circular design in diameter 87mm.

Protection rating against dust and moisture: IP65 from underneath.

Double trim of die-cast aluminium and flush glass, sealed with a silicone gasket.

Tempered protection glass clear as standard, other finishes under request.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Remote driver included.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0,4.

Imax=1764 Cd

η=100.0% ▼ M ▼ Ø ▼ LUX

2 1.30

3 1.95 196

4 2.6 110

0.65 1763

36°

Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable

upgrades, ease maintenance and extend the product lifecycle. Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted by spring clamps for easy installation.

Luminaire luminous flux: 840lm Luminaire connected power: 7,25 W Luminaire efficiency: 116 lm/W Light source luminous flux: 840lm Light source power: 6,5 W Constant Current: 200 mA

CRI: >90 R9 54

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 36° **LOR:** 100%

LED reliability at nominal Ta = 25°C: 54.000h L90B10

UGR: $C0^{\circ} = 17,1 \mid C90^{\circ} = 16,6 \mid C90^{\circ} = 16,6$

Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 0

Cd/Klm: 2100

This product contains a light source of energy efficiency class F

Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC, NOT looping through capable)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDiM/corridorFUNCTION DE: DALI-2/switchDIM + 3h battery B: Bluetooth-Casambi

*Add the suffix -K. -S. -SE. -D. -DE. -B after the reference to indicate your electronic equipment choice.

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 10.12.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13