




101STL.1-I2100



Surface-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.
Neutral cylindrical body in diameter 190mm.
Adjustable to 20° and 180°+180° rotation.
Aluminium reflector in assorted finishes: specular metalized, faceted metalized or sandblasted metalized depending on the beam angle outcome.
Powder painted aluminium body available in assorted finishes, customized RAL under request.
Built-in driver, included.
Electronic options for lighting control: DALI-2 or Bluetooth.
The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.
Mounting to the ceiling plate with two securing points.
Cable entry from the top of the fixture.
SATELLITE can be combined with the BASE surface mounted line to get a harmonious finish.

Luminaire luminous flux: 2120lm
Luminaire connected power: 17,1 W
Luminaire efficiency: 124 lm/W
Light source luminous flux: 2330lm
Light source power: 15,43 W
Constant Current: 500 mA
CRI: >90 R9 64
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 12°
LOR: 91%
LED reliability at nominal Ta = 25°C: 100.000h L90B10
Photobiological safety group: 1
Cd/Klm: 9093
This product contains a light source of energy efficiency class D




Electronic Equipment
S: On/Off (AC/DC, NOT looping through capable)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi

*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 09.09.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com