


102QDM.1-R2013



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or general lighting.

Square frameless design for plasterboard ceilings available in 180mm x 180mm.

Powder painted aluminium frame available in assorted finishes, customized RAL under request. To complete the effect of this fixture, it is also recommended that the inner shade should be painted the same RAL colour as the ceiling.

High-purity matt anodised aluminium reflector to obtain the best photometric results.

Remote driver supplied.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

3 hours battery available as option (class I).

Passive temperature management: heat dissipation flows through aluminium heatpipes.

Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.

- Luminaire luminous flux:** 2624lm
- Luminaire connected power:** 24,2 W
- Luminaire efficiency:** 108 lm/W
- Light source luminous flux:** 4100lm
- Light source power:** 21,8 W
- Constant Current:** 700 mA
- CRI:** >80
- Colour Temperature:** 3000K
- Chromaticity Tolerance:** MacAdam 3
- Beam Angle:** 64°
- LOR:** 64%
- LED reliability at nominal Ta = 25°C:** 60.000h L90B10
- Photobiological safety group:** 1
- Cd/Klm:** 584

This product contains a light source of energy efficiency class C


Electronic Equipment

- K:** On/Off (basic)
- S:** On/Off (AC/DC + looping through)
- SE:** On/Off (AC/DC+looping) + 3h battery
- D:** DALI-2/switchDIM/corridorFUNCTION
- DE:** DALI-2/switchDIM/corridorFUNCTION + Battery 3h
- B:** Bluetooth-Casambi


*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.08.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com