

SPLASH







101SPS.1.01-R2034



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Circular design in diameter 190mm.

Protection rating against dust and moisture: complete IP54.

Sandblasted metalized aluminium reflector.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. Tempered protection glass clear as standard, other finishes under request.

Remote driver supplied.


Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

Passive temperature management: heat dissipation flows through aluminium heat sink. Ceiling-mounted by three fixing points.

Luminaire luminous flux: 1238lm

Luminaire connected power: 11,9 W Luminaire efficiency: 104 lm/W Light source luminous flux: 1650lm Light source power: 10,66 W Constant Current: 350 mA CRI: >90 R9 64 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 77° LOR: 75%



LED reliability at nominal Ta = 25°C: 60.000h L90B50 | 57.000h L90B10 Photobiological safety group: 1 Cd/Klm: 591

This product contains a light source of energy efficiency class D

Electronic Equipment

K: On/Off (basic)
S: On/Off (AC/DC, NOT looping through capable)
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -K, -S, -D after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.09.2025]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com