

η=99.9% ▼ M ▼ Ø ▼ LUX

0.64 1553

1.28 388


1.91

3.2 62

1

4 2.6 97 35°





## 140GTA.1-I1862









Surface mounted downlights with symmetrical light distribution to achieve an effective task or general

Neutral cylindrical body in diameter 60mm.

Sandblasted metalized aluminium reflector silver finished.

Powder painted aluminium profile available in assorted finishes, customized RAL under request.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.

Imax=1554 Cd

Mounting to the ceiling plate with two securing points. Cable entry from the top of the fixture. GOTA can be combined with the KERI pendant line to get a harmonious finish.

Luminaire luminous flux: 641lm Luminaire connected power: 5,15 W Luminaire efficiency: 124 lm/W Light source luminous flux: 855lm Light source power: 4,64 W Constant Current: 150 mA

**CRI:** >80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 35° **LOR:** 75%

LED reliability at nominal Ta = 25°C: 60.000h L90B10

Photobiological safety group: 1

## **Electronic Equipment**

S: On/Off (AC/DC, NOT looping through capable)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

1: RAL9010: Pure White textured, 2: RAL9005: Jet Black textured, 4: RAL7016: Anthracite Grey textured, 7: RAL9006:

## Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.** 

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com

Spain