
TIRET 800

IP40 Projectors







851TRT.1-I1468



IP40 650°





Linear projectors or uplights with symmetrical light distribution to achieve an effective task or general

Linear fixture in 566mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal extruded polycarbonate diffuser. Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

lmax=474 Cd

180

270

η=100.0% ▼M ▼Ø ▼LUX

1

2 4.1

3 6.1 53

4 8.2

5 10.2 19.0

2.0 474

119

91°

limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management.

Wall mounted by adjustable mounting brackets.

Matching products:

TIRET 100 recessed.

TIRET 200 frameless recessed.

TIRET 300 surface mounted.

TIRET 400 and TIRET 500 pendant.

TIRET 600 and TIRET 700 wall-mounted.

TIRET 800 projectors.

Luminaire luminous flux: 1074lm Luminaire connected power: 12,02 W Luminaire efficiency: 89 lm/W Light source luminous flux: 1705lm Light source power: 10,82 W Constant Current: 250 mA

CRI: >90 R9 57

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 91° **LOR:** 63%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 0

Cd/Klm: 443

This product contains a light source of energy efficiency class D

Electronic Equipment

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13

^{*}Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.