
TIRET 800







851TRT.1-I1471





Linear projectors or uplights with symmetrical light distribution to achieve an effective task or general

Linear fixture in 566mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal extruded polycarbonate diffuser. Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

lmax=745 Cd

200

300

400

500

η=100.0% ▼M ▼Ø ▼LUX

1

2 4.1

3 6.1 83

4 8.2

5 10.2 30

2.0 745

186

91°

limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management.

Wall mounted by adjustable mounting brackets.

Matching products:

TIRET 100 recessed.

TIRET 200 frameless recessed.

TIRET 300 surface mounted.

TIRET 400 and TIRET 500 pendant.

TIRET 600 and TIRET 700 wall-mounted.

TIRET 800 projectors.

Luminaire luminous flux: 1742lm Luminaire connected power: 17,1 W Luminaire efficiency: 102 lm/W Light source luminous flux: 2765lm Light source power: 15,4 W Constant Current: 350 mA

CRI: >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 91° **LOR:** 63%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 1

Cd/Klm: 443

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off (AC/DC, NOT looping through capable)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Contact

T. +34 93 881 35 12

info@rovasi.com

T. +34 93 881 37 13 www.rovasi.com

^{*}Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.