## RAINA 100 IP40 Recessed linear downlights



	150RNA.1-I2435 IP40 650° +RAL ************************************
	Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 306mm length and in a width of 68mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker
3 <sub>4</sub>	limits: PstLM ≤ 1 and SVM ≤ 0.4. Passive temperature management. Ceiling-mounted using steel support with screws. End caps must be ordered separately, reference M5.E0068. It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.Q0068.
306	Luminaire luminous flux: $600 \text{ Imax} = 219 \text{ Cd}$ $n = 100.0\%$ VM VØ VLUX $103^{\circ}$ Luminaire efficiency: $76 \text{ Im}/W$ Light source luminous flux: $1000 \text{ Im}$ Light source power: $5,41 \text{ W}$ Constant Current: $250 \text{ mA}$ CRI: $>80$ Colour Temperature: $2700 \text{ K}$ Chromaticity Tolerance: MacAdam 3 Beam Angle: $103^{\circ}$ LOR: $60\%$
<sup>10</sup> []68 ]68	LED reliability at nominal Ta = 25°C: 100.000h L80B10 Photobiological safety group: 0 This product contains a light source of energy efficiency class C Electronic Equipment
	<ul> <li>S: On/Off</li> <li>D: DALI-2/switchDIM</li> <li>B: Bluetooth-Casambi</li> <li>*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.</li> </ul>
	Finishes 1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium
	Upgradeable, Replaceable, Repairable
s.	

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.06.2025]
5 years guarantee

СЕ BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

## Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com