## BARIS 300 IP54 Surface mounted linear downlights



351BRS.1-I1458 +RAL IK08 650° **IP54** Surface mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 568mm length and in a width of 44mm. Protection rating against dust and moisture: complete IP54. Protection rating of resistance to harmful mechanical impacts: IK08. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4. Passive temperature management. Ceiling-mounted using cleats. 78 Luminaire luminous flux: 686lm nax=265 Cd η=100.0% ▼M ▼Ø ▼LUX 100° 568 Luminaire connected power: 7,08 W 2.4 264 1 Luminaire efficiency: 97 lm/W 2 4.8 66 Light source luminous flux: 1295lm 100 Light source power: 6,4 W 3 29 7.2 150 Constant Current: 150 mA 4 9.6 16.5 200 **CRI:** >80 Colour Temperature: 4000K 5 12.0 10.6 Chromaticity Tolerance: MacAdam 3 Beam Angle: 100° LOR: 53% LED reliability at nominal Ta = 25°C: 100.000h L80B10 Photobiological safety group: 0 Cd/Klm: 399 ]]44 This product contains a light source of energy efficiency class C 568 **Electronic Equipment** S: On/Off (AC/DC) DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi \*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. Finishes 1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium Upgradeable, Replaceable, Repairable 

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 21.05.2025]

**CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com