
BARIS 600








650BRS.1-I1429



lighting. Linear fixture in 287mm length and in a width of 44mm. Protection rating against dust and moisture: complete IP54. Protection rating of resistance to harmful mechanical impacts: IK08. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2 or Bluetooth. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management. Wall mounted by mounting brackets. Accessory for serial installation, reference F3.L6.BRS. Luminaire luminous flux: 323lm Imax=132 Cd η=100.0% ▼M ▼Ø ▼LUX 100°

Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general

Luminaire connected power: 5,7 W Luminaire efficiency: 57 lm/W Light source luminous flux: 610lm Light source power: 3,2 W Constant Current: 150 mA **CRI:** >80 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 100° LOR: 53% LED reliability at nominal Ta = 25°C: 100.000h L80B10 Photobiological safety group: 0 This product contains a light source of energy efficiency class C



Electronic Equipment

S: On/Off D: DALI-2/switchDIM B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 10.09.2025]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com