BARIS 600







650BRS.1-I1446



IP54 **IK08**







Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general

Linear fixture in 287mm length and in a width of 44mm.

Protection rating against dust and moisture: complete IP54.

Protection rating of resistance to harmful mechanical impacts: IK08.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

lmax=247 Cd

135

η=100.0% ▼ M ▼ Ø ▼LUX

1 2.4

2 4.8 62

3 7.2 27

4

100°

247

15.4 9.6

12.0 9.9

limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management. Wall mounted by mounting brackets.

Accessory for serial installation, reference F3.L6.BRS.

Luminaire luminous flux: 625lm Luminaire connected power: 10,2 W Luminaire efficiency: 61 lm/W Light source luminous flux: 1180lm

Light source power: 7,7 W Constant Current: 350 mA

CRI: >90 R9 57

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 100°

LOR: 53%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 1

This product contains a light source of energy efficiency class D

Electronic Equipment

S: On/Off

D: DALI-2/switchDIM

B: Bluetooth-Casambi

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 30.07.2025]

5 years guarantee



Spain

T. +34 93 881 37 13

 $^{^{\}star}$ Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.