BARIS 600







651BRS.1-I1457



IP54 **IK08**







Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general

Linear fixture in 568mm length and in a width of 44mm.

Protection rating against dust and moisture: complete IP54.

Protection rating of resistance to harmful mechanical impacts: IK08.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

lmax=253 Cd

η=100.0% ▼ M ▼ Ø ▼LUX

2 4.8 63

3 7.2 28

4

2.4 253

15.8 9.6

12.0 10.1

100°

limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management. Wall mounted by mounting brackets.

Accessory for serial installation, reference F3.L6.BRS.

Luminaire luminous flux: 647lm Luminaire connected power: 7,08 W Luminaire efficiency: 91 lm/W Light source luminous flux: 1220lm

Light source power: 6,4 W Constant Current: 150 mA

CRI: >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 96° **LOR:** 53%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 0

Cd/Klm: 399

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off (AC/DC, NOT looping through capable) **D:** DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASIS.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13

^{*}Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.