BARIS 600







661BRS.1-I1462



IP54 **IK08**







Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general

Linear fixture in 568mm length and in a width of 44mm.

Protection rating against dust and moisture: complete IP54.

Protection rating of resistance to harmful mechanical impacts: IK08.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Microprismatic polycarbonate diffuser.

Highly efficient linear printed circuit board. Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

nax=367 Cd

η=100.0% ▼M ▼Ø ▼LUX

2

3 6.9

4 9.2 23

2.3 367

11.5

92 4.6

41

limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management.

Accessory for serial installation, reference F3.L6.BRS.

Luminaire luminous flux: 738lm Luminaire connected power: 7,08 W Luminaire efficiency: 104 lm/W Light source luminous flux: 1085lm

Light source power: 6,4 W Constant Current: 150 mA

CRI: >90 R9 54

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 98° **LOR:** 68%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 0

Cd/Klm: 499

Electronic Equipment

S: On/Off (AC/DC, NOT looping through capable)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 06.08.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.**

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13