## GOWEL 100 IP20 Recessed linear downlights



	131GWL.1-I1710
	IP20 IK06 650° +RAL Image: State of the sta
	Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 597mm length and in a width of 84mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.
34. <u>597</u> ]65	Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized systems.
597	Luminaire luminous flux: 1651mImage: 180 ministre connected power: 11,4 with source power: 18,6 kith source power: 8,8 with 1775lmImage: 180 ministre connected power: 150 mAImage: 170 ministre connected power: 150 ministre connected powe
	Upgradeable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 06.07.2025]

5 years guarantee CC BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

## Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com