GOWEL 200 IP20 Frameless recessed linear downlights



	230GWL.1-I1700
	IP20 IK06 650° +RAL +MODULAR 296 x 73mm
	Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Frameless linear fixture in 295mm length and in a width of 70mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker
[<u>⊢</u> <u>⊢</u>]65 	 limits: PstLM ≤ 1 and SVM ≤ 0.4. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized systems.
290	Luminaire luminous flux: 78.1lmImage: Connected powe: 7.WImage: Connected powe: 7.W
	Upgradeable, Repairable

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.07.2025]

E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.**

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com