
# GOWEL 800







### 801GWL.1-I1717



Linear projectors with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 581mm length and in a width of 70mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4. Passive temperature management. Ceiling or wall mounted using adjustable supports. Matching products: GOWEL 100 recessed with frame. GOWEL 200 frameless recessed. GOWEL 300 surface mounted. GOWEL 400 pendant. Luminaire luminous flux: 5187lm η=100.0% ▼M ▼Ø ▼LUX 17° 32940 Cd Luminaire connected power: 35.5 W 0.30 32940 1 Luminaire efficiency: 146 lm/W 2 0.60 8235 Light source luminous flux: 5700lm Light source power: 32 W 3 0.91 3660 Constant Current: 500 mA 4 1.21 2059 **CRI:** 80 Colour Temperature: 5000K 1.51 1318 5 Chromaticity Tolerance: MacAdam 3 Beam Angle: 17° LOR: 91% LED reliability at nominal Ta = 25°C: 72.000h L80B10 Photobiological safety group: 1 Cd/Klm: 6350 This product contains a light source of energy efficiency class C **Electronic Equipment** S: On/Off (AC/DC, NOT looping through capable) D: DALI-2/switchDIM/corridorFUNCTION B: Bluetooth-Casambi \*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. Finishes 1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.07.2025]

## 5 years guarantee

**L C** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASI S.L.** Ronda de la Font Grossa, 15

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com