GOWEL 900



	900GWL.1-I1703 Image: Description of the system of the system. Base of the system of	
]65]295	Luminaire luminous flux: 1502lm Luminaire connected power: 12,1 W Luminaire efficiency: 124 lm/W Light source luminous flux: 1650lm Light source power: 9,1 W Constant Current: 300 mA CRI: 80 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 17° LOR: 91% LED reliability at nominal Ta = 25°C: 72.000h L80 Photobiological safety group: 1 This product contains a light source of energy e	Imax=9538 Cd n=100.0% M VØ VLUX 17° 1 0.30 9538 1 0.30 9538 1 1 2 0.60 2385 3 0.91 1060 1000 4 1.21 596 5 1.51 382
	Electronic Equipment S: On/Off D: DALI-2/switchDIM B: Bluetooth-Casambi *Add the suffix -S, -D, -B after the reference to indicate your electron Finishes 1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016	
	Upgradeable, Replaceable, Repairable	

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.07.2025]

СЕ BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com