GOWEL 900



	901GWL.1-I1716
	IP20 IK06 650° IK06 650°
	Linear downlights with three-phase track adapter. Symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 581mm length and in a width of 70mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4. Passive temperature management. Three-phase tracks are available as well as accessories to create a custom system.
[]65	Luminaire luminous flux: 5187lm Luminaire connected power: 35,5 W Luminaire efficiency: 146 lm/W Light source luminous flux: 5700lm Light source power: 32 W Constant Cummants 500 m 0
581	Constant Current: 500 mA
Note	

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.07.2025]

5 years guarantee CC BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com