



153MUR.4.01-I1484



Recessed wall mounted fixtures with symmetrical light distribution. Linear fixture in 885mm length, width of 75mm and height of 100mm. Protection rating against dust and moisture: complete IP66. Protection rating for resistance to harmful mechanical impacts: IK10. Extruded aluminium profile coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request. Highly efficient linear printed circuit board. Protection polycarbonate diffuser in 4mm. Interior frosted polycarbonate diffuser. Built-in driver, included. Ambient temperature: up to 50°C. Electronic options for lighting control: DALI-2 or Bluetooth. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0,4. Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle. IP67 venting valve to reduce condensation. A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw. Mounting to the wall by two securing points. Recessing case included. Pre-wiring of 35cm cable 3x1mm<sup>2</sup>. The electric cable inlet is on one end of the luminaire. Passive temperature management.



**Luminaire luminous flux:** 826lm  
**Luminaire connected power:** 10,62 W  
**Luminaire efficiency:** 78 lm/W  
**Light source luminous flux:** 1835lm  
**Light source power:** 9,6 W  
**Constant Current:** 150 mA  
**CRi:** >80  
**Colour Temperature:** 2700K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 96°  
**LOR:** 45%

**LED reliability at nominal Ta = 25°C:** 100.000h L80B10

**Photobiological safety group:** 0

**Cd/Klm:** 449

**This product contains a light source of energy efficiency class C**


#### Electronic Equipment

**S:** On/Off (AC/DC, NOT looping through capable)  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**B:** Bluetooth-Casambi [ 15m ]


\*Add the suffix **-S, -D, -B** after the reference to indicate your electronic equipment choice.

#### Finishes

**4:** RAL7016: Anthracite Grey textured, **1:** RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **7:** RAL9006: White Aluminium textured, **80 Corten:** **90:** RAL6005 Moss Green textured



#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.01.2026]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
 BSI Cert ISO 14001:2015 - n°EMS 554685

#### ROVASI S.L.

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

#### Contact

T. +34 93 881 35 12 info@rovashi.com  
 T. +34 93 881 37 13 [www.rovashi.com](http://www.rovashi.com)