

731DST.4.01-I1477



Wall mounted linear fixtures with symmetrical light distribution.

Double light emission: up and down.

Linear fixture in 575mm length, width of 62mm and height of 138mm.

Protection rating against dust and moisture: complete IP66.

Protection rating for resistance to harmful mechanical impacts: IK10.

Extruded aluminium profile coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.

Highly efficient linear printed circuit board.

Protection polycarbonate diffuser in 4mm.

Interior optic to control the light.

Built-in driver.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0,4.

Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle.

IP67 venting valve to reduce condensation.

A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw.

Wall-mounted by 316L stainless steel mounting brackets.

The electric cable inlet is on one end of the luminaire. luminaires can also be supplied with two cable inlets, one on each side, for serial installation, reference F3.L6.DST.

The driver is on the inside of the fixture.

Passive temperature management.

It is possible to specify individual luminous flux, beam angle and colour temperature for each luminaire side, downlight and uplight side.

Luminaire luminous flux: 2x2936lm

Luminaire connected power: 2x22,31 W

Luminaire efficiency: 132 lm/W

Light source luminous flux: 2x3495lm

Light source power: 2x20,08 W

Constant Current: 450 mA

CRI: >80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 41°


LOR: 84%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 1

Cd/Klm: 815

This product contains a light source of energy efficiency class C



Electronic Equipment

S: On/Off (AC/DC, NOT looping through capable)

D: DALI-2/switchDIM/corridorFUNCTION


B: Bluetooth-Casambi [15m]

*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

4: RAL7016: Anthracite Grey textured, **1:** RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **7:** RAL9006: White Aluminium textured, **80 Corten:**, **90:** RAL6005 Moss Green textured

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.12.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com