KAUTTA 100 IP40 Recessed linear downlights



136KTA.1-I1540 +RAL IP40 650° 1414 x 47mm Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting. Linear fixture in 1426mm length and in a width of 58mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optics for controlling and directing the light. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4. 3 hours battery available as option. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. 78 Other options available: 1426 Frameless recessed. Surface mounted. Pendant. Wall-mounted. Projector. It is possible to combine different lengths and junction modules in different ways to create customized design. Luminaire luminous flux: 2846lm Imax=2055 Cd η=93.4% ▼M ▼Ø ▼LUX 43° Luminaire connected power: 17,71 W 1 0.79 2053 Luminaire efficiency: 161 lm/W 1.58 513 2 Light source luminous flux: 3060lm Light source power: 16 W]58 3 2.4 228 Constant Current: 150 mA 128 4 3.2 1426 **CRI:** >80 Colour Temperature: 2700K 5 3.9 82 Chromaticity Tolerance: MacAdam 3 Beam Angle: 43° LOR: 93% LED reliability at nominal Ta = 25°C: 100.000h L80B10 Photobiological safety group: 0 Cd/Klm: 704 This product contains a light source of energy efficiency class C **Electronic Equipment** S: On/Off (AC/DC) SE: On/Off (AC/DC) + Batterv 3h DE: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM+ 3 hours battery DDE: DALI-2/switchDIM+ 3 hours battery (DALI) B: Bluetooth-Casambi *Add the suffix -S, -SE, -D, -DE, -DDE, -B after the reference to indicate your electronic equipment choice. **Finishes** 1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium Upgradeable, Replaceable, Repairable $-(LED) \rightarrow \rightarrow (LED)$

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.05.2025]

CE BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15 T. Pol. Ind. La Gavarra T.

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com