
# KAUTTA 400

## IP20 Pendant linear downlights







### 430KTA.1-I1431



Pendant linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting.

Linear fixture in 287mm length and in a width of 44mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optics for controlling and directing the light.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits:  $PstLM \le 1$  and  $SVM \le 0.4$ .

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request.

Other options available:

Recessed.

Frameless recessed.

Surface mounted.

Wall-mounted.

It is possible to combine different lengths and junction modules in different ways to create customized design.

η=96.0% ▼ M

1 0.75 423

2 1.50 106

3 2.3

4 3.0 26

▼Ø ▼LUX

3.8 16.9

47

41°

Luminaire luminous flux: 600lm Luminaire connected power: 5,7 W Luminaire efficiency: 105 lm/W Light source luminous flux: 645lm Light source power: 3,2 W Constant Current: 150 mA

**CRI:** >80

Colour Temperature: 5000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 41°

**LOR:** 93%

**LED reliability at nominal Ta = 25°C:** 100.000h L80B10 **UGR:**  $C0^{\circ} = 19.5 \mid C90^{\circ} = 25$  under the below indicated parameters Room dimensions X=4H/8H

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 0

**Cd/Klm:** 704

This product contains a light source of energy efficiency class B

#### **Electronic Equipment**

S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

#### Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.11.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685 **ROVASIS.L.** 

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com

**Contact** , 15 T. +34 93 881 3