
# KAUTTA 800

## **IP40 Projectors**







#### 831KTA.1-I1459



IP40 650°



Linear projectors with symmetrical light distribution to achieve an effective accent, task or general

Linear fixture in 568mm length and in a width of 44mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optics for controlling and directing the light.

Highly efficient linear printed circuit board. Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

lmax=887 Cd

η=93.4% ▼ M ▼ Ø ▼ LUX

1.58

3.9 35

98 2.4

1 0.79 886

3

4 3.2 55 43°

limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4. Passive temperature management.

Ceiling or wall installation with adjustable fixing brackets.

Other options available:

Recessed.

Frameless recessed.

Surface-mounted.

Pendant. Wall-mounted.

Luminaire luminous flux: 1195lm Luminaire connected power: 7,08 W Luminaire efficiency: 169 lm/W Light source luminous flux: 1285lm

Light source power: 6,4 W Constant Current: 150 mA

**CRI:** >80

Colour Temperature: 5000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 43° **LOR:** 93%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 0

**Cd/Klm:** 704

This product contains a light source of energy efficiency class B

### **Electronic Equipment**

S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

\*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 06.07.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.** 

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

Contact

T. +34 93 881 37 13