# KAUTTA 900

## Linear downlights with track adapter



η=93.4% ▼ M ▼ Ø ▼ LUX

2

3 2.3

4

0.75

1.50 102

3.8 16.4

26 3.0





### 930KTA.1-I1429



Highly efficient linear printed circuit board.

Linear downlights with three-phase track adapter. Symmetrical light distribution to achieve an effective accent, task or general lighting.

Linear fixture in 287mm length and in a width of 44mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optics for controlling and directing the light.

Built-in driver, included.

Electronic options for lighting control: DALI-2 or Bluetooth.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM  $\leq$  1 and SVM  $\leq$  0.4.

Passive temperature management.

Three-phase tracks are available as well as accessories to create a custom system.

Luminaire luminous flux: 567lm Luminaire connected power: 5,7 W Luminaire efficiency: 99 lm/W Light source luminous flux: 610lm Light source power: 3,2 W Constant Current: 150 mA

**CRI:** >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 43° **LOR:** 93%

LED reliability at nominal Ta = 25°C: 100.000h L80B10  $\mbox{\bf UGR:}~C0^{o}=19,3\mid C90^{o}=24,8\,$  under the below indicated parameters Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.25m

Photobiological safety group: 0

**Cd/Klm:** 704

This product contains a light source of energy efficiency class C

#### **Electronic Equipment**

D: DALI-2/switchDIM/corridorFUNCTION

#### **Finishes**

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 01.11.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.** 

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

info@rovasi.com www.rovasi.com

T. +34 93 881 35 12 T. +34 93 881 37 13

<sup>\*</sup>Add the suffix -S, -D after the reference to indicate your electronic equipment choice.