
CAPELLA 300

Surface-mounted downlights







311CPL.01.00-I2165



Surface-mounted downlights with symmetrical light distribution to achieve an effective task or ambient

Lampshade in diameter 550mm.

Silicone optic to control and direct the light.

Lampshade and aluminium body liquid painted with textured finish.

Select from a vast range of colours and finishes to perfectly customize your fittings. Whether you prefer a single colour or want to create a unique combination, we offer flexible options. You can choose a RAL colour for the exterior of your lampshade and pair it with various finishes for the interior.

Removable lampshade that can be easily replaced with another design or finish.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker

limits: PstLM \leq 1 and SVM \leq 0,4.

Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle.

Passive temperature management: heat dissipation flows through aluminium heat sink.

Mounting to the ceiling plate with two securing holes. Cable entry from the top of the luminaire.

Luminaire luminous flux: 972lm Luminaire connected power: 11,9 W Luminaire efficiency: 82 lm/W Light source luminous flux: 1620lm Light source power: 10,66 W Constant Current: 350 mA

CRI: >90 R9 62

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 71° **LOR:** 60%

LED reliability at nominal Ta = 25°C: 60.000h L90B10

Photobiological safety group: 1

This product contains a light source of energy efficiency class E

Electronic Equipment

S: On/Off (AC/DC, NOT looping through capable)
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

η=99.8% ▼ M ▼ Ø ▼LUX 1.43 612 1 2 2.9 153 300 3 68 4.3 400 5.7 4 38 7.1 24

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 15.12.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.**

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com

Spain





Colour options

Lampshade and aluminium body liquid painted with textured finish. Select from a vast range of colours to perfectly customize your fittings.

One single colour



1: RAL9010 Pure White textured



2: RAL9005 Jet Black textured



13: RAL 1023
Traffic Yellow textured



14: RAL 1037 Sun Yellow textured



15: RAL 2012 Salmon Orange textured



16: RAL 3000 Flame red textured



17: RAL 5024 Pastel Blue textured



18: RAL 5003 Sapphire Blue textured



19: RAL 6018 Yellow Green textured



20: RAL 6000 Patina Green textured



21: RAL 8001: Ochre Brown textured



22: RAL8016 Mahogany Brown textured

CAPELLA

Pendant downlights



Two colours combined / outer and inner

Select from a vast range of colours to perfectly customize your fittings. You can choose a RAL colour for the exterior of your lampshade and pair it with various finishes for the interior.

Inner finishes.









21: RAL 8001: Ochre Brown textured 20: RAL9005 Jet Black textured



18: RAL 5003 Sapphire Blue textured 10: RAL9010 Pure White textured




22: RAL8016 Mahogany Brown textured 30: Golden


REFERENCE COMPOSITION




Structure of a standard reference:




Product Section | Luminaire with one single colour



Product Section | Luminaire with two colours combined: outer and inner



Light source and driver section



ROVASI S.L.

Spain