
ADHARA







421ADH.01.00-R2080



IP20 750°







Pendant downlights with symmetrical light distribution to achieve an effective task or ambient lighting. Lampshade in diameter 560mm.

Silicone optic to control and direct the light.

Lampshade and aluminium body liquid painted with textured finish.

Select from a vast range of colours and finishes to perfectly customize your fittings. Whether you prefer a single colour or want to create a unique combination, we offer flexible options. You can choose a RAL colour for the exterior of your lampshade and pair it with various finishes for the interior.

Removable lampshade that can be easily replaced with another design or finish.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

lmax=1255 Cd

Passive temperature management: heat dissipation flows through aluminium heat sink.

Delivered with 1 meter steel cord suspension as standard and black electronic wire. Mounted to the ceiling with a recessed base with two fixing points..

Luminaire luminous flux: 2663lm Luminaire connected power: 24,2 W Luminaire efficiency: 110 lm/W Light source luminous flux: 4295lm Light source power: 21,8 W Constant Current: 700 mA

CRI: >80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 95° **LOR:** 62%

LED reliability at nominal Ta = 25°C: 60.000h L90B10

Photobiological safety group: 1

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off (AC/DC, NOT looping through capable)

D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice.

500 3 6.6 139 750 4 78 8.8 5 11.0 50

η=99.8% ▼ M ▼ Ø ▼LUX

1

2 4.4 314

2.2 1254

96°

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.09.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.**

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13



ROVASI Positive Lighting

Colour options

Lampshade and aluminium body liquid painted with textured finish. Select from a vast range of colours to perfectly customize your fittings.

One single colour



1: RAL9010 Pure White textured



2: RAL9005 Jet Black textured



13: RAL 1023
Traffic Yellow textured



14: RAL 1037 Sun Yellow textured



15: RAL 2012 Salmon Orange textured



16: RAL 3000 Flame red textured



17: RAL 5024 Pastel Blue textured



18: RAL 5003 Sapphire Blue textured



19: RAL 6018 Yellow Green textured



20: RAL 6000 Patina Green textured



21: RAL 8001: Ochre Brown textured



22: RAL8016 Mahogany Brown textured

ADHARA

Pendant downlights



Two colours combined / outer and inner

Select from a vast range of colours to perfectly customize your fittings. You can choose a RAL colour for the exterior of your lampshade and pair it with various finishes for the interior.

Inner finishes.



Some inspirations.



Ochre Brown textured

20: RAL9005

Jet Black textured



ROVASI S.L.

Sapphire Blue textured

10: RAL9010

Pure White textured

Mahogany Brown textured

30: Golden


Patina Green textured

40: Copper


REFERENCE COMPOSITION




Structure of a standard reference:




Product Section | Luminaire with one single colour



Product Section | Luminaire with two colours combined: outer and inner



Light source and driver section



ROVASI S.L.