


## IP65 Klein Einbau-Downlights



|                                                                                   |      |      |      |                                                                                        |                                                                                        |                                                                                          |                                                                                   |
|-----------------------------------------------------------------------------------|------|------|------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
|  | IP65 | IK05 | 850° |  +RAL |  78mm |  0.36Kg |  |
|-----------------------------------------------------------------------------------|------|------|------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|

Deckenmontierte verzinkte Stahlhalterung mit Federklammern.

$I_{\max}=2112 \text{ Cd}$        $\eta=99.9\%$       ▼ M    ▼ Ø    ▼ LUX      21°

|   |      |      |
|---|------|------|
| 1 | 0.36 | 2112 |
| 2 | 0.73 | 528  |
| 3 | 1.09 | 235  |
| 4 | 1.45 | 132  |
| 5 | 1.82 | 84   |

**1:** RAL9010: Reinweiß, **2:** RAL9005: Tiefschwarz, **4:** RAL7016: Anthrazitgrau, **7:** RAL9006: Weißaluminium

CE

BSI Cert ISO 14001:2015 - n°EMS 554685

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spanien

T. +34 93 881 35 12  
T. +34 93 881 37 13

**www.rovasi.com**