

101HDN.1-R2330



Recessed ceiling-mounted multidirectional downlights with symmetrical light distribution to achieve an effective task, accent or general lighting.

Square design in 110mm x 110mm.

Swivel mounted downlights, adjustable up to 25° and with 180° rotation.

Die-cast aluminium trim and recessing surface powder painted in assorted finishes, customized RAL under request.

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Electronic options for lighting control: DALI-2.


The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0.4.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted with spring clamps for easy installation.

- Luminaire luminous flux:** 1115lm
- Luminaire connected power:** 11,13 W
- Luminaire efficiency:** 100 lm/W
- Light source luminous flux:** 1115lm
- Light source power:** 9,98 W
- Constant Current:** 300 mA
- CRI:** >90 R9 52
- Colour Temperature:** 2700K
- Chromaticity Tolerance:** MacAdam 3
- Beam Angle:** 24°
- LOR:** 100%
- LED reliability at nominal Ta = 25°C:** 54.000h L90B10
- Photobiological safety group:** 0
- Cd/Klm:** 4291
- This product contains a light source of energy efficiency class F**



Electronic Equipment


- K:** On/Off (basic)
- S:** On/Off (AC/DC)
- SE:** On/Off (AC/DC) + Battery 3h
- D:** DALI-2/switchDIM/corridorFUNCTION
- DE:** DALI-2/switchDIM + 3h battery
- B:** Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.05.2025]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarrà
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com