
# PINHOLE SEAL IP65 Small recessed downlights





## 125PNS.1.01-R2309



Small recessed ceiling-mounted downlight with asymmetrical light distribution to achieve an effective accent lighting. Protection rating against dust and moisture: IP65 from underneath. Circular design in diameter 85mm, slot interior aperture with 17mm radius. Internal cylindrical aluminium black baffle for minimal glare. Deep regressed module to ensure visual comfort. Adjustable baffle, tilt up to 30°. Powder painted trim available in assorted finishes, customized RAL under request. Glass and silicone rubber gasket to ensure IP65 protection from underneath. Remote driver included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits:  $PstLM \le 1$  and  $SVM \le 0.4$ . 3 hours battery available as option. Passive temperature management: heat dissipation flows through an aluminium heat sink. Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm. Luminaire connected power: 7,25 W Light source luminous flux: 685lm Light source power: 6,68 W Constant Current: 200 mA CRI: >90 R9 54 Colour Temperature: 2700K Chromaticity Tolerance: MacAdam 3 Beam Angle: 12° LED reliability at nominal Ta = 25°C: >54000h L90B50 Photobiological safety group: 1 This product contains a light source of energy efficiency class F **Electronic Equipment** 

K: On/Off (basic) S: On/Off (AC/DC) SE: On/Off (AC/DC) + Battery 3h D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM + 3h battery B: Bluetoth-Casambi

\*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

#### Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 15.06.2025]

### 5 years guarantee

**L C** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASI S.L.** Ronda de la Font Grossa, 15

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

**Contact** T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com