KIBRI 300



350KBR.11-I2904 IP20 650° Surface mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 284mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. White finish modular optics in 7 cells designed to ensure visual comfort. Blind covers available with a length of 280mm or its multiples: accessory reference M5.Y. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4. Passive temperature management. Ceiling-mounted using cleats. It is possible to combine different lengths and junction modules in different 69 ways to create customized design. 284 Luminaire luminous flux: 1245lm η=99.9% ▼M ▼Ø ▼LUX Imax=824 Cd 79° Luminaire connected power: 12.5 W 1 1.64 820 Luminaire efficiency: 100 lm/W 2 3.3 205 Light source luminous flux: 1270lm 300 Light source power: 8,8 W 3 4.9 91 450 Constant Current: 450 mA 4 6.5 51 600 **CRI:** 90 750 Colour Temperature: 2700K 5 8.2 33 Chromaticity Tolerance: MacAdam3 Beam Angle: 78° LOR: 98% LED reliability at nominal Ta = 25°C: 72.000h L80B10 Photobiological safety group: 1 This product contains a light source of energy efficiency class D **Electronic Equipment** S: On/Off D: DALI-2/switchDIM B: Bluetooth-Casambi *Add the suffix -S, -D, -B after the reference to indicate your electronic equipment choice. Finishes 11: White frame - white reflector Upgradeable, Replaceable, Repairable (<u>2</u>

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.08.2025]

CE BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com