


150PNT.4.01-I1437



Lighting structure for ground illumination with symmetrical light distribution. Luminaire height 300mm, customized height under request. Protection rating against dust and moisture: IP66 – full protection. Protection rating for resistance against harmful mechanical impacts: IK10. Extruded aluminium body coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request. 4mm frontal polycarbonate diffuser. Interior opal diffuser. IP67 venting valve to reduce condensation. Silicone gasket. Highly efficient linear printed circuit board. Built-in driver included. Ambient temperature: up to 50°C. Electronic options for light control: DALI-2 or Bluetooth. The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM ≤ 1 and SVM ≤ 0,4. Luminaire designed according to ecodesign principles, with replaceable light source and driver, to enable upgrades, ease maintenance and extend the product lifecycle. A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws. IP68 connector not included, it can be ordered separately: F3.A3 (On/Off) / F3.A5 (DALI-2). Pre-wiring of 15cm cable 3x1mm². Mounting plate for floor installation supplied with the fixture. Sturdy base accessory to ensure high stability in public space F3.2.TRPN.

Luminaire luminous flux: 509lm
Luminaire connected power: 7,9 W
Luminaire efficiency: 64 lm/W
Light source luminous flux: 1060lm
Light source power: 5,41 W
Constant Current: 250 mA
CRI: >80
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 96°
LOR: 48%

LED reliability at nominal Ta = 25°C: 100.000h L80B10

Photobiological safety group: 0

This product contains a light source of energy efficiency class B


Electronic Equipment

S: On/Off
D: DALI-2/switchDIM
B: Bluetooth-Casambi [15m]


*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

4: RAL7016: Anthracite Grey textured, **1:** RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **7:** RAL9006: White Aluminium textured, **80 Corten:** **90:** RAL6005 Moss Green textured



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 10.01.2026]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
 Pol. Ind. La Gavarra
 08540 Centelles | Barcelona
 Spain

Contact

T. +34 93 881 35 12 info@rovashi.com
 T. +34 93 881 37 13 www.rovashi.com