

## 101FLW.1-R237



Semi-recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective ambient lighting.

Blown glass sphere available in assorted finishes, customized colour under request.

Protection rating against dust and moisture: IP54 from underneath.

Clear glass fixture screwed into an aluminium body sealed with a silicone trim.

Remote driver supplied.

Electronic standard options for lighting control: DALI/DSI.

Emergency kit as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted with spring clamps for easy installation, ceiling thicknesses up to .mm.

**Luminaire connected power:** 4.8 W

**Light source luminous flux:** 760lm

**Constant Current:** 150 mA

**CRI:** >80

**Colour Temperature:** 2700K

**Chromaticity Tolerance:** MacAdam 3

**Average Service Life:** 50000h

**LED reliability:** 56000h L80B10

**Photobiological safety group:** 1

**This product contains a light source of energy efficiency class A++**

### Electronic Equipment


**D:** DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

### Finishes

**1:** RAL9010: Pure White

### Upgradeable, Replaceable, Repairable



### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

### ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

### Contact

T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 **www.rovasi.com**