

101MQD.1-R681



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.
Circular design in diameter 110mm.
Sandblasted metalized aluminium reflector.
Powder painted die-cast aluminium trim available in assorted finishes.
Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0110].
Remote driver supplied. Electronic options for lighting control: DALI-2.
Passive temperature management: heat dissipation flows through heat sink.
Ceiling-mounted using galvanised steel support with spring clamps.


Luminaire luminous flux: 1376lm
Luminaire connected power: 11.8 W
Luminaire efficiency: 117 lm/W
Light source luminous flux: 1930lm
Constant Current: 350 mA
CRI: >80
Colour Temperature: 4000K
Chromaticity Tolerance: MacAdam3
Beam Angle: 82°
LOR: 71%
Average Service Life: 50000h
LED reliability: 51000h L80B10
UGR: >21 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 1m
Photobiological safety group: 1
Cd/Klm: 638
Imax: 878 Cd

This product contains a light source of energy efficiency class A++

Electronic Equipment
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

Finishes
2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 02.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarrà
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com