DYNAMIC OPTIMAL DISPLAY



Adjustable recessed downlights



165

18

Ø165

Ø129

105DNM.1-R687



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or accent lighting.

Adjustable to 20° and 180°+180° rotation.

Circular design in diameter 165mm. Aluminium reflector in assorted finishes: facetted metalized or sandblasted metalized depending on the beam angle outcome.


Powder painted aluminium trim available in assorted finishes, customized RAL under request.

Remote driver supplied. LED module for special applications.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink diffuser. Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 40mm.

Luminaire luminous flux: 1337lm Luminaire connected power: 18,33 W Light source luminous flux: 1470lm Light source power: 17 W Constant Current: 500 mA CRI: >90 Colour Temperature: GOLD+ Chromaticity Tolerance: MacAdam 4 Beam Angle: 12° LOR: 91% Average Service Life: 50000h LED reliability: 51000h L80B10 Photobiological safety group: 1 Cd/KIm: 9093



This product contains a light source of energy efficiency class $\,\mathrm{G}$

Electronic Equipment

K: On/Off (basic) S: On/Off (AC/DC + looping through) SE: On/Off (AC/DC + looping) + 3h battery D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h B: Bluetooth-Casambi

*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.05.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com