

TUNABLE WHITE

Special Applications









106TOP.1.02-I722









Pendant downlights with symmetrical light distribution to achieve an effective ambient lighting. Circular design in 1100mm diameter.

Powder painted aluminium profile available in assorted finishes, customized RAL under request. Polycarbonate opal diffuser (thickness 3mm.)

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 2700K - 6500K Built-in driver, included.

Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI-2.

The driver contained in this luminaire complies with European Directive 2009/125/EC establishing flicker limits: PstLM \leq 1 and SVM \leq 0.4.

Passive temperature management: heat dissipation flows through the fixture body itself.

Delivered with a short powder painted metal rod, custom made length up to 1000mm, minimum 300mm. Mounted to the ceiling by cylindrical ceiling rose.

TOP can be combined with the LEDA surface-mounted fixtures and KUU and CANDRA recessed mounted lines to get an harmonious finish.

Luminaire connected power: 102 W Light source luminous flux: 17020lm

Light source power: 102 W Constant Current: 250 mA

CRI: >90

Colour Temperature: 2700K-6500K Chromaticity Tolerance: MacAdam 3 Average Service Life: 50000h LED reliability: 50000h L90B50 Photobiological safety group: 1

This product contains a light source of energy effic

Electronic Equipment

T: DALI-2/switchDIM/ColourSwitch

*Add the suffix -T after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.**

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com