
## TUNABLE WHITE

## Special Applications















Surface-mounted downlights with symmetrical light distribution to achieve an effective ambient lighting. Circular design available in 835mm diameter.

Powder painted one piece aluminium profile available in assorted finishes, customized RAL under request.

Polycarbonate opal diffuser (thickness 3mm.).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 3000K - 6000K Built-in driver, included.

Electronic standard options for lighting control: SwitchDIM/ColourSwitch/DALI-2.

3 hours battery available as option (change of size required).

Passive temperature management: heat dissipation flows through the fixture body itself.

Mounting to the ceiling plate with four securing points. Cable entry from the top of the fixture.

LEDA can be combined with PLACE pendant downlights and KUU and CANDRA recessed downlights to

get a harmonious finish.

Light source luminous flux: 9610lm Light source power: 58 W Constant Current: 250 mA

**CRI:** >90

Colour Temperature: 2700K-6500K Chromaticity Tolerance: MacAdam 3 Average Service Life: 50000h LED reliability: 50000h L90B50 Photobiological safety group: 1

Luminaire connected power: 58 W

This product contains a light source of energy effic



1180

T: DALI-2/switchDIM/ColourSwitch

 $^{\star}\mathrm{Add}$  the suffix -T after the reference to indicate your electronic equipment choice.

## Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

## 17-\frac{\overline{\overline{\sigma}835}{\overline{\sigma}800}}{\overline{\sigma}800}

835

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 17.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685 **ROVASIS.L.** 

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com