

TUNABLE WHITE



Special Applications







104KUU.1.02-I720



Recessed ceiling mounted downlights with symmetrical light distribution to achieve an effective ambient lighting.

Circular design available in 596mm diameter.

Powder painted aluminium trim available in assorted finishes, customized RAL under request. Polycarbonate opal diffuser (thickness 3mm).

Tridonic high energy efficiency printed circuit board. Tunable White PCB: 3000K - 6000K Built-in driver, included.

Electronic options for lighting control: SwitchDIM/ColourSwitch/DALI-2.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through the fixture body itself.

Ceiling-mounted using galvanised steel support with screws, ceiling thickness up to 30mm.

KUU can be combined with PLACE pendant downlights and LEDA surface-mounted downlights to get a harmonious finish.

Luminaire connected power: 28 W Light source luminous flux: 4650lm Light source power: 28 W Constant Current: 125 mA CRI: >90 Colour Temperature: 2700K-6500K Chromaticity Tolerance: MacAdam 3 Average Service Life: 5000h LED reliability: 5000h L90B50 Photobiological safety group: 1 This product contains a light source of energy effic

Electronic Equipment T: DALI-2/switchDIM/ColourSwitch

*Add the suffix -T after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 08.05.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com